



Ultrafuse® rPET

Sustainability Meets High Performance

No less than 44 % of total waste* is generated by plastics. The 3D printing community provides a powerful opportunity to make current manufacturing methods more sustainable, so we have challenged ourselves to create a filament made from recycled material that is a serious alternative to filaments made from virgin raw materials.

We are now proud to say that with the new Ultrafuse® rPET we have more than met the challenge. The “r” stands for recycled, as Ultrafuse® rPET is made from recycled PET medical equipment. Components printed with Ultrafuse® rPET print, look and perform as outstandingly as our PET filament made from virgin raw material

Benefits at a Glance

- Sustainable alternative to PET
- Easy to print
- Great end results

Example Applications

- Jigs & fixtures
- Automotive parts
- Prototyping

Material Properties

Tensile strength (MPa)	14.7 (ZX), 38.6 (XY)
Flexural modulus (MPa)	829(ZX), 1551 (XZ), 1662 (XY)
Elongation (Break)	1.2 % (ZX), 4.3 % (XY)
Impact strength Izod notched (kJ/m²)	1.5 (ZX), 3.3 (XZ), 4.4 (XY)
Impact strength Izod unnotched (kJ/m²)	4.4 (ZX), 21.9 (XZ), 48.2 (XY)
HDT @ 0.45 MPa	71°C

Printing Guidelines

Nozzle Temperature	225-245 °C
Bed Temperature	65-85 °C
Nozzle Diameter	≥0.4 mm
Bed Modification	Adhesive spray or glue
Print Speed	30-60 mm/s
Drying	Vacuum dryer or hot air, dryer 60°C for 4-16 hours

The product data is provided in good faith and represents typical properties based on our current knowledge and experience; these data are not to be construed as specification limits or minimum values. Product properties may be changed without notice. This document does not create any liability, warranty or guarantee of product performance. It is the buyer's responsibility to determine the suitability of Ultrafuse® products for the intended application.

